



## General Information

---

In many industrial sectors and fields of research, temperature measurement is one of the most important parameters which determines product quality, security, and reliability. Temperature sensors are available in several types all of which have a unique performance characteristic. The performance capability of the various sensors are a result of the manufacturing process and component materials associated with their technologies and intended application. It is IST Charter to produce sensors that exceed the industry standard of temperature measurement with additional capability to directly replace older traditional methods and provide the maximum performance. To this end IST has concentrated its development and manufacturing on the process and materials of high-end thin-film temperature sensors. Additionally these processes, partially derived from the semiconductor industry allows IST to manufacture sensors in very small dimensions. Because of their low thermic mass thin-film temperature sensors exhibit a very short response time. IST core technology and processes results in thin-film sensors that combine the good features of traditional wire wound platinum sensors such as accuracy, long-term stability, repeatability, interchangeability and wide temperature range, with the advantages of mass-production, which contributes to their optimal price/performance ratio.

## Sensor Construction

---

The temperature sensor consists of a photo-lithographically structured, high-purity platinum coating arranged in the shape of a meander. The platinum thin-film structures are laser trimmed to form resistive paths with very precisely defined basic value of the resistivity. The sensors are covered with a glass passivation layer; to protect the sensor against mechanical and chemical damage. The bonded leadwires which are additionally covered with a drop of glass make electrical contacts to the resistive structure.

## Typical Features

---

- brief response time
- excellent long-term stability
- low self-heating rate
- excellent price/performance ratio
- small dimensions
- resistant against vibration and temperature shocks
- simple interchangeability

## Response Time

---

The response time  $T_{0.63}$  is the time in seconds the sensors need to respond to 63% of the change in temperature. The response time depends on the sensor dimensions, the thermal contact resistance and the enclosure medium.

## Long-Term Stability

---

The change of ohmage after 1,000 hrs at maximum operating temperature until the 7W types amounts to less than 0.03%.

## Self Heating

---

To measure the resistance an electric current has to flow through the element, which will generate heat energy resulting in errors of measurement. To minimize the error, the testing current should be kept low (approximately 1 mA for pt-100). Temperature error  $\Delta T = RI^2 / E$ ; with E = self-heating coefficient in mW/K R = resistance in k $\Omega$ , I = measuring current in mA

## Measurement current

---

The amount of thermal transfer from the sensor in application determines how much measuring current can be applied. There is no bottom limit of the measurement current with platinum thin-film. The measurement current depend highly on the application in use. For sensors from 750°C - 1000°C (7W, 8W, 10W) the measurement current must limited at max. 1 mA.

We recommend at:

|                  |             |             |
|------------------|-------------|-------------|
| 100 $\Omega$ :   | typ. 1 mA   | max. 5 mA   |
| 500 $\Omega$ :   | typ. 0.5 mA | max. 3 mA   |
| 1000 $\Omega$ :  | typ. 0.3 mA | max. 2 mA   |
| 2000 $\Omega$ :  | typ. 0.2 mA | max. 1 mA   |
| 10000 $\Omega$ : | typ. 0.1 mA | max. 0.3 mA |



## Nominal values

The nominal or rated value of the sensor is the target value of the sensor resistance at 0° C. The temperature coefficient  $\alpha$  is defined

as  $\alpha = \frac{R_{100} - R_0}{100 \cdot R_0}$  [K<sup>-1</sup>] and has the numerical value of 0.00385 K<sup>-1</sup> according to DIN IEC 751.

In practice, a value multiplied by 10<sup>6</sup> is often entered: TCR = 10<sup>6</sup> \*  $\frac{R_{100} - R_0}{100 \cdot R_0}$  [ppm/K].  
In this case, the numerical value is 3850 ppm/K.

## Temperatur Characteristic Curve

The characteristic temperature curve determines the dependence of the electrical resistivity on the temperature. The following definition of the temperature curve according to the DIN EN 60751 standard applies:

$$-200 \text{ bis } 0^\circ\text{C} \quad R(t) = R_0 (1 + A \cdot t + B \cdot t^2 + C \cdot [t-100] \cdot t^3)$$


$$0 \text{ bis } 850^\circ\text{C} \quad R(t) = R_0 (1 + A \cdot t + B \cdot t^2)$$

Platinum (3850 ppm/K):  
A = 3.9083 \* 10<sup>-3</sup> [°C<sup>-1</sup>]; B = -5.775 \* 10<sup>-7</sup> [°C<sup>-2</sup>];  
C = -4.183 \* 10<sup>-12</sup> [°C<sup>-4</sup>]

Platinum (3750 ppm/K):  
A = 3.8102 \* 10<sup>-3</sup> [°C<sup>-1</sup>]; B = -6.01888 \* 10<sup>-7</sup> [°C<sup>-2</sup>];  
C = -6 \* 10<sup>-12</sup> [°C<sup>-4</sup>]

Platinum (3770 ppm/K):  
A = 3.92 \* 10<sup>-3</sup> [°C<sup>-1</sup>]; B = -6.03 \* 10<sup>-7</sup> [°C<sup>-2</sup>];

R<sub>0</sub> = Resistance value in ohm at 0°C;  
t = temperature in accordance with ITS 90



Tolerance field

## Tolerance Classes

temperature sensors are divided into classes according to their limit deviations:

| Class                   | +/- limit deviations in °C (K) | IST AG designation | area of validity of temperature class |
|-------------------------|--------------------------------|--------------------|---------------------------------------|
| DIN 60751, class B      | 0.30 + 0.005 x   t             | B                  | -200°C bis 850°C                      |
| DIN 60751, class A      | 0.15 + 0.002 x   t             | A                  | -90°C bis 300°C                       |
| ½ DIN 60751, class B    | 0.10 + 0.0017 x   t            | Y                  | -50°C bis 150°C                       |
| 2DIN 60751, class B     | 0.60 + 0.01 x   t              | C                  | -200°C bis 850°C                      |
| 1/5 DIN 60751, class B  | 0.06 + 0.001 x   t             | 1/5                | on request                            |
| 1/10 DIN 60751, class B | 0.03 + 0.0005 x   t            | 1/10               | on request                            |

| t | is the numerical value of the temperature in °C without taking into account either negative or positive signs.  
Special selection of sensors upon request (e.g. pairings, grouping, special tolerances)



## Response Times and Self-Heating

| Dimension Number | Sensor Size<br>L x W x T / H in mm | Response Time in seconds |                   |                  |                  |                   |                  | Self-Heating       |         |                  |         |
|------------------|------------------------------------|--------------------------|-------------------|------------------|------------------|-------------------|------------------|--------------------|---------|------------------|---------|
|                  |                                    | Water 0.4 m/s            |                   |                  | Air 1m/s         |                   |                  | Water<br>v = 0 m/s |         | Air<br>v = 0 m/s |         |
|                  |                                    | T <sub>0.5</sub>         | T <sub>0.63</sub> | T <sub>0.9</sub> | T <sub>0.5</sub> | T <sub>0.63</sub> | T <sub>0.9</sub> | mW/K               | ΔT[mK]* | mW/K             | ΔT[mK]* |
| MiniSens 161     | 1.6 x 1.2 x 0.25 / 0.9             | 0.05                     | 0.08              | 0.18             | 1                | 1.2               | 2.5              | 12                 | 8.3     | 1.8              | 56      |
| SlimSens 308     | 3.0 x 0.8 x 0.25 / 0.6             | 0.08                     | 0.10              | 0.25             | 1.2              | 1.5               | 3.5              | 15                 | 6.7     | 2.2              | 46      |
| 232              | 2.3 x 2.0 x 0.25 / 0.9             | 0.09                     | 0.12              | 0.33             | 2.7              | 3.6               | 7.5              | 40                 | 2.5     | 4                | 25      |
| 202              | 2.0 x 2.0 x 0.63 / 1.3             | 0.12                     | 0.18              | 0.42             | 4                | 5.4               | 11               | 36                 | 2.8     | 3.6              | 28      |
| 216              | 2.0 x 1.6 x 0.63 / 1.3             | 0.11                     | 0.16              | 0.38             | 3.6              | 4.9               | 10.2             | 32                 | 3.1     | 3.2              | 31      |
| 232              | 2.3 x 2.0 x 0.63 / 1.3             | 0.15                     | 0.2               | 0.55             | 4.5              | 6                 | 12               | 40                 | 2.5     | 4                | 25      |
| 325              | 3.0 x 2.5 x 0.63 / 1.3             | 0.25                     | 0.3               | 0.7              | 5.5              | 7.5               | 16               | 90                 | 1.1     | 8                | 13      |
| 516              | 5.0 x 1.6 x 0.63 / 1.3             | 0.25                     | 0.3               | 0.7              | 5.5              | 7.5               | 16               | 80                 | 1.3     | 7                | 14      |
| 520              | 5.0 x 2.0 x 0.63 / 1.3             | 0.25                     | 0.3               | 0.75             | 6                | 8.5               | 18               | 80                 | 1.3     | 7                | 14      |
| 525              | 5.0 x 2.5 x 0.63 / 1.3             | 0.33                     | 0.4               | 0.85             | 6.5              | 9                 | 19               | 90                 | 1.1     | 8                | 13      |
| 538              | 5.0 x 3.8 x 0.63 / 1.3             | 0.35                     | 0.4               | 0.9              | 7.5              | 10                | 20               | 140                | 0.7     | 10               | 10      |
| 505              | 5.0 x 5.0 x 0.63 / 1.3             | 0.4                      | 0.5               | 1.1              | 8                | 11                | 21               | 150                | 0.7     | 11               | 9       |
| 102              | 10.0 x 2.0 x 0.63 / 1.3            | 0.33                     | 0.4               | 0.85             | 7.5              | 10.5              | 20               | 140                | 0.7     | 10               | 10      |
| 281              | 1 x 13 x Ø 2.8                     | 2.5                      | 4.5               | 8                | 10               | 15                | 28               | 60                 | 1.7     | 5.5              | 18      |
| 281              | 2 x 13 x Ø 2.8                     | 2                        | 2.5               | 5.5              | 10               | 12                | 22               | 45                 | 2.2     | 4                | 25      |
| 451              | 1 x 13 x Ø 4.5                     | 8                        | 10                | 22               | 12               | 22                | 40               | 85                 | 1.2     | 8                | 13      |
| 451              | 2 x 13 x Ø 4.5                     | 5                        | 6                 | 14               | 16               | 18                | 37               | 60                 | 1.7     | 6.5              | 15      |
| SMD 1206         | 3.2 x 1.6 x 0.4                    | 0.15                     | 0.25              | 0.45             | 3.5              | 4.2               | 10               | 55                 | 1.8     | 7                | 14      |
| SMD 0805         | 2.0 x 1.2 x 0.4                    | 0.10                     | 0.12              | 0.33             | 2.5              | 3                 | 8                | 38                 | 2.6     | 4                | 25      |
| FC 0603          | 1.5 x 0.75 x 0.4                   | 0.08                     | 0.10              | 0.25             | 1.8              | 2.2               | 5.5              | 25                 | 4       | 2.5              | 40      |

\*self heating ΔT[mK] measured for Pt100 at 1mA measurement current at 0°C

L: Chip length (sensor length without connections)  
W: Sensor width

T: Chip thickness (sensor thickness without connections)  
H: Sensor height (incl. connections and strain relief)

Notification: The values in the table are of informative nature only. Due to different measurement conditions you might assess deviant self heating and response time values of your application.

### Tolerances of dimensions

|                               |                        |
|-------------------------------|------------------------|
| Sensor width (W) ± 0.2 mm     | Wire length ± 1.0 mm   |
| Sensor length (L) ± 0.2 mm    | Tube length ± 0.2 mm   |
| Sensor height (H) ± 0.3 mm    | Tube diameter ± 0.1 mm |
| Sensor thickness (T) ± 0.1 mm |                        |



## 1P - Product Series

Temperature Range: -60°C... +150°C

### Temperature sensors in SMD construction

Soldering depot, RoHS conform (reflow solderable) \*only Flip Chip assembly

#### Technical Data


|                               |  |
|-------------------------------|--|
| Temperature range:            | -50°C to +150°C (1P, 2P) ; -50°C to +250°C (3P, 4P)  |
| Classes:                      | Pt: DIN class A; DIN class B; 2x DIN class B   |
| Soldering connection:         | Contacts:<br>1P = Contacts tin coated (62Sn/36Pb/2Ag), LMP lead contained<br>2P = Contacts tin coated (96.5Sn/3Ag/0.5Cu), LMP lead free, RoHS conform<br>3P = Contacts tin coated (5Sn/93.5Pb/1.5Ag), HMP, RoHS conform<br>4P = Contacts gold plated, solderable film<br>- there is no insurance for DIN class A,<br>due to the changed resistance value after soldering.<br>- bondable contacts without bumps available on request. |
| Solderability:                | 235°C ≤ 8s (DIN IEC 68 2-20, Ta Meth 1)  |
| Resistance to soldering heat: | 260°C 10x (DIN IEC 68 2-20, Ta Meth. 1A)   |
| Long-term stability:          | Pt: max. Drift = 0.04% after 1000h at 130°C  |

#### Dimensions in mm


#### Nominal Resistance at 0°C in Ohm

#### Chip-Dimensions in mm


#### Description



|      |               |                |
|------|---------------|----------------|
| 100  | LxW 2.0 x 1.2 | P0K1.0805.xP.x |
| 500  | LxW 2.0 x 1.2 | P0K5.0805.xP.x |
| 1000 | LxW 2.0 x 1.2 | P1K0.0805.xP.x |



|      |               |                |
|------|---------------|----------------|
| 100  | LxW 3.2 x 1.6 | P0K1.1206.xP.x |
| 500  | LxW 3.2 x 1.6 | P0K5.1206.xP.x |
| 1000 | LxW 3.2 x 1.6 | P1K0.1206.xP.x |



|      |                |                  |
|------|----------------|------------------|
| 100  | LxW 1.5 x 0.75 | P0K1.0603.xFC.x* |
| 500  | LxW 1.5 x 0.75 | P0K5.0603.xFC.x* |
| 1000 | LxW 1.5 x 0.75 | P1K0.0603.xFC.x* |



## 1S - Product Series

Temperature Range: -60°C... +150°C


Temperature sensors with SIL-Contacts (solderable, crimpable), 10 mm long

Dimensions  
in mm

Nominal Resistance  
at 0°C in Ohm

Chip-Dimensions  
in mm


Description



100  
500  
1000

LxW 3.0 x 2.5  
LxW 3.0 x 2.5  
LxW 3.0 x 2.5


P0K1.325.1S.x  
P0K5.325.1S.x  
P1K0.325.1S.x



100  
500  
1000

LxW 5.0 x 2.5  
LxW 5.0 x 2.5  
LxW 5.0 x 2.5


P0K1.525.1S.x  
P0K5.525.1S.x  
P1K0.525.1S.x



100  
500  
1000

LxW 5.0 x 3.8  
LxW 5.0 x 3.8  
LxW 5.0 x 3.8

P0K1.538.1S.x  
P0K5.538.1S.x  
P1K0.538.1S.x



100  
500  
1000

LxW 5.0 x 5.0  
LxW 5.0 x 5.0  
LxW 5.0 x 5.0

P0K1.505.1S.x  
P0K5.505.1S.x  
P1K0.505.1S.x

## 2S – Product Series

Temperature Range:  $-60^{\circ}\text{C} \dots +200^{\circ}\text{C}$

Temperature sensors with SIL-Contacts (solderable, crimpable), 10 mm long

| Dimensions<br>in mm | Nominal Resistance<br>at 0°C in Ohm | Chip-Dimensions<br>in mm       | Description                    |
|---------------------|-------------------------------------|--------------------------------|--------------------------------|
|                     | 100<br>1000                         | LxW 3.0 x 2.5<br>LxW 3.0 x 2.5 | P0K1.325.2S.x<br>P1K0.325.2S.x |
|                     | 100<br>1000                         | LxW 5.0 x 2.5<br>LxW 5.0 x 2.5 | P0K1.525.2S.x<br>P1K0.525.2S.x |
|                     | 100<br>1000                         | LxW 5.0 x 3.8<br>LxW 5.0 x 3.8 | P0K1.538.2S.x<br>P1K0.538.2S.x |
|                     | 100<br>1000                         | LxW 5.0 x 5.0<br>LxW 5.0 x 5.0 | P0K1.505.2S.x<br>P1K0.505.2S.x |







## 3FW - Product Series

Temperature Range: -200...+300°C

### Temperature sensors with Flat Wire (FW) connections

Ni/Au wire 0.2 x 0.4 x 7/10 mm (H x W x L), (solderable, weldable, crimpable)

| Dimensions<br>in mm   | Nominal Resistance<br>at 0°C in Ohm | Chip-Dimensions<br>in mm                        | Description  |
|---|-------------------------------------|---|--|
|    | 100<br>1000                         | LxW 2.5 x 1.6<br>LxW 2.5 x 1.6                  | P0K1.216.3FW.x.x<br>P1K0.216.3FW.x.x                     |
|   | 100<br>500<br>1000                  | LxW 2.0 x 2.0<br>LxW 2.0 x 2.0<br>LxW 2.0 x 2.0 | P0K1.202.3FW.x.x<br>P0K5.202.3FW.x.x<br>P1K0.202.3FW.x.x |
|  | 100<br>500<br>1000                  | LxW 2.3 x 2.0<br>LxW 2.3 x 2.0<br>LxW 2.3 x 2.0 | P0K1.232.3FW.x.x<br>P0K5.232.3FW.x.x<br>P1K0.232.3FW.x.x |
|  | 10'000                              | LxW 5.0 x 2.0                                   | P10K.520.3FW.010   |








## 4W - Product Series


Temperature Range: -200°C...+400°C

### Temperature sensors with wire connections


Silver wire connection 0.25 mm x 10 mm (Ø x L), (solderable, weldable)

| Dimensions in mm  | Nominal Resistance at 0°C in Ohm | Chip-Dimensions in mm  | Description  |
|---|----------------------------------|--|--|
|    | 100<br>500<br>1000               | LxW 1.6 x 1.2<br>LxW 1.6 x 1.2<br>LxW 1.6 x 1.2                  | P0K1.161.4W.x.010<br>P0K5.161.4W.x.010<br>P1K0.161.4W.x.010                      |
|   | 100<br>500<br>1000<br>2000       | LxW 2.0 x 2.0<br>LxW 2.0 x 2.0<br>LxW 2.0 x 2.0<br>LxW 2.0 x 2.0 | P0K1.202.4W.x.010<br>P0K5.202.4W.x.010<br>P1K0.202.4W.x.010<br>P2K0.202.4W.x.010 |
|  | 100                              | LxW 2.5 x 1.6  | P0K1.216.4W.x.010  |
|  | 100<br>500<br>1000<br>2000       | LxW 2.3 x 2.0<br>LxW 2.3 x 2.0<br>LxW 2.3 x 2.0<br>LxW 2.3 x 2.0 | P0K1.232.4W.x.010<br>P0K5.232.4W.x.010<br>P1K0.232.4W.x.010<br>P2K0.232.4W.x.010 |
|  | 100<br>500<br>1000<br>2000       | LxW 5.0 x 1.6<br>LxW 5.0 x 1.6<br>LxW 5.0 x 1.6<br>LxW 5.0 x 1.6 | P0K1.516.4W.x.010<br>P0K5.516.4W.x.010<br>P1K0.516.4W.x.010<br>P2K0.516.4W.x.010 |





|        |               |                   |
|--------|---------------|-------------------|
| 100    | LxW 5.0 x 2.0 | P0K1.520.4W.x.010 |
| 500    | LxW 5.0 x 2.0 | P0K5.520.4W.x.010 |
| 1000   | LxW 5.0 x 2.0 | P1K0.520.4W.x.010 |
| 10'000 | LxW 5.0 x 2.0 | P10K.520.4W.x.010 |



|      |                |                   |
|------|----------------|-------------------|
| 100  | LxW 10.0 x 2.0 | P0K1.102.4W.x.010 |
| 500  | LxW 10.0 x 2.0 | P0K5.102.4W.x.010 |
| 1000 | LxW 10.0 x 2.0 | P1K0.102.4W.x.010 |

## 6W – Product Series

Temperature Range: -200°C...+600°C

### Temperature sensors with wire connections


Platinum clad (coated) nickel wire, 0.2 mm x 10 mm (Ø x L), (solderable, weldable, crimpable)

Dimensions  
in mm


Nominal Resistance  
at 0°C in Ohm

Chip-Dimensions  
in mm

Description




|      |               |                   |
|------|---------------|-------------------|
| 100  | LxW 1.6 x 1.2 | P0K1.161.6W.x.010 |
| 500  | LxW 1.6 x 1.2 | P0K5.161.6W.x.010 |
| 1000 | LxW 1.6 x 1.2 | P1K0.161.6W.x.010 |



|      |               |                   |
|------|---------------|-------------------|
| 100  | LxW 3.0 x 0.8 | P0K1.308.7W.x.007 |
| 500  | LxW 3.0 x 0.8 | P0K5.308.7W.x.007 |
| 1000 | LxW 3.0 x 0.8 | P1K0.308.7W.x.007 |


(Pure Platinum wire 0.15 mm diameter)



|      |               |                   |
|------|---------------|-------------------|
| 100  | LxW 2.0 x 2.0 | P0K1.202.6W.x.010 |
| 500  | LxW 2.0 x 2.0 | P0K5.202.6W.x.010 |
| 1000 | LxW 2.0 x 2.0 | P1K0.202.6W.x.010 |
| 2000 | LxW 2.0 x 2.0 | P2K0.202.6W.x.010 |




# Platinum Temperature Sensors



100  
1000

LxW 2.5 x 1.6  
LxW 2.5 x 1.6


P0K1.216.6W.x.010  
P1K0.216.6W.x.010



100  
500  
1000  
2000

LxW 2.3 x 2.0  
LxW 2.3 x 2.0  
LxW 2.3 x 2.0  
LxW 2.3 x 2.0


P0K1.232.6W.x.010  
P0K5.232.6W.x.010  
P1K0.232.6W.x.010  
P2K0.232.6W.x.010



100  
500  
1000  
2000

LxW 5.0 x 1.6  
LxW 5.0 x 1.6  
LxW 5.0 x 1.6  
LxW 5.0 x 1.6


P0K1.516.6W.x.010  
P0K5.516.6W.x.010  
P1K0.516.6W.x.010  
P2K0.516.6W.x.010



100  
500  
1000  
10'000

LxW 5.0 x 2.0  
LxW 5.0 x 2.0  
LxW 5.0 x 2.0  
LxW 5.0 x 2.0


P0K1.520.6W.x.010  
P0K5.520.6W.x.010  
P1K0.520.6W.x.010  
P10K.520.6W.x.010



100  
1000

LxW 5.0 x 3.8  
LxW 5.0 x 3.8

P0K1.538.6W.x.010  
P1K0.538.6W.x.010



100  
500  
1000

LxW 10.0 x 2.0  
LxW 10.0 x 2.0  
LxW 10.0 x 2.0

P0K1.102.6W.x.010  
P0K5.102.6W.x.010  
P1K0.102.6W.x.010



## 7W – Product Series

Temperature Range: -200°C...+750°C

### Temperature sensors with wire connections


With Platinum wire 0.2 mm x 7 mm (Ø x L), (solderable, weldable, crimpable)

Dimensions  
in mm

Nominal Resistance  
at 0°C in Ohm

Chip-Dimensions  
in mm


Description



100  
1000

LxW 1.6 x 1.2  
LxW 1.6 x 1.2


P0K1.161.7W.x.007  
P1K0.161.7W.x.007



100  
1000

LxW 2.3 x 2.0  
LxW 2.3 x 2.0


P0K1.232.7W.x.007  
P1K0.232.7W.x.007



100  
500  
1000

LxW 5.0 x 1.6  
LxW 5.0 x 1.6  
LxW 5.0 x 1.6


P0K1.516.7W.x.007  
P0K5.516.7W.x.007  
P1K0.516.7W.x.007



100  
500  
1000

LxW 5.0 x 2.0  
LxW 5.0 x 2.0  
LxW 5.0 x 2.0

P0K1.520.7W.x.007  
P0K5.520.7W.x.007  
P1K0.520.7W.x.007



100  
500  
1000

LxW 10.0 x 2.0  
LxW 10.0 x 2.0  
LxW 10.0 x 2.0

P0K1.102.7W.x.007  
P0K5.102.7W.x.007  
P1K0.102.7W.x.007



## 8W – Product Series

Temperature Range: -200°C...+850°C

Temperature sensors with wire connections


Platinum wire 0.2 mm x 7 mm (Ø x L), (solderable, weldable, crimpable)

Dimensions  
in mm

Nominal Resistance  
at 0°C in Ohm

Chip-Dimensions  
in mm


Description



100  
500  
1000

LxW 5.0 x 1.6  
LxW 5.0 x 1.6  
LxW 5.0 x 1.6

P0K1.516.8W.x.007  
P0K5.516.8W.x.007  
P1K0.516.8W.x.007



100  
500  
1000

LxW 4.0 x 2.0  
LxW 4.0 x 2.0  
LxW 4.0 x 2.0

P0K1.420.8W.x.007  
P0K5.420.8W.x.007  
P1K0.420.8W.x.007

## 10W – Product Series

Temperature Range: -70°C...+1000°C

Temperature sensors with wire connections

Platinum wire 0.2 mm x 7 mm (Ø x L), (solderable, weldable, crimpable)


Temperature dependence 3770 ppm/K

Dimensions  
in mm

Nominal Resistance  
at 0°C in Ohm

Chip-Dimensions  
in mm

Description



200

LxW 4.0 x 2.0

P0K2.420.10W.K.007



# Platinum Temperature Sensors



## 4SW – Product Series

Temperature Range: -200°C...+400°C

Temperature sensors with perpendicular leads


Silver wire connections 0.25 mm x 10 mm (Ø x L), (solderable, weldable)

Dimensions  
in mm

Nominal Resistance  
at 0°C in Ohm

Chip-Dimensions  
in mm

Description



100  
1000

LxW 1.6 x 1.2  
LxW 1.6 x 1.2

P0K1.161.4SW.x.010  
P1K0.161.4SW.x.010



100  
500  
1000

LxW 2.3 x 2.0  
LxW 2.3 x 2.0  
LxW 2.3 x 2.0

P0K1.232.4SW.x.010  
P0K5.232.4SW.x.010  
P1K0.232.4SW.x.010

## T – Product Series

Temperature Range: -200°C...+600°C

Temperature sensors on a thin substrate for short response time


Platinum wire Nickel coated 0.2 mm x 10 mm (Ø x L), (solderable, weldable, crimpable)

Dimensions  
in mm

Nominal Resistance  
at 0°C in Ohm

Chip-Dimensions  
in mm

Description



100  
500  
1000

LxW 2.3 x 2.0  
LxW 2.3 x 2.0  
LxW 2.3 x 2.0

P0K1.232.6W.x.010.T  
P0K5.232.6W.x.010.T  
P1K0.232.6W.x.010.T



# Platinum Temperature Sensors



## R – Product Series

Temperature Range: -50°C...+600°C

### Temperature sensors in ceramic tubes


Platinum wire Nickel coated 0.2 mm x 7 mm (Ø x L), (solderable, weldable, crimpable)

Dimensions  
in mm

Nominal Resistance  
at 0°C in Ohm

Chip-Dimensions  
in mm


Description



100  
500  
1000

LxW 13.0 x 4.5  
LxW 13.0 x 4.5  
LxW 13.0 x 4.5


P0K1.451.6W.x.R  
P0K5.451.6W.x.R  
P1K0.451.6W.x.R



100  
500  
1000

LxW 13.0 x 4.5  
LxW 13.0 x 4.5  
LxW 13.0 x 4.5

2xP0K1.451.6W.x.R  
2xP0K5.451.6W.x.R  
2xP1K0.451.6W.x.R



100  
500  
1000

LxW 13.0 x 2.8  
LxW 13.0 x 2.8  
LxW 13.0 x 2.8

P0K1.281.6W.x.R  
P0K5.281.6W.x.R  
P1K0.281.6W.x.R



100  
500  
1000

LxW 13.0 x 2.8  
LxW 13.0 x 2.8  
LxW 13.0 x 2.8

2xP0K1.281.6W.x.R  
2xP0K5.281.6W.x.R  
2xP1K0.281.6W.x.R



## CustomSens


### Thin-film temperature sensors with universal connection possibilities

It is the policy of IST to put forward as many sensor options as possible to best serve the customers needs. True to this policy is the CustomSens product. We are bringing a new range of sensors on to the market which will provide enormous versatility. The highlight of these thin-film temperature sensors is the flexibility of determining your own wire termination type or style as required. You can decide how much work we should take off your hands in the assembly of the sensors. You can choose between short or long connections, whether they are to be bare or insulated and whether the sensor is to be completed in 2-, 3- or even 4-wire technology. It is not only the great choice of these variables which offers you many advantages. Through the customized connection structure, the sensors are also characterized by superior product properties, giving you a double benefit.

### Universal possibilities

Below you will find all the variables at a single glance. When you combine these with your requirement profile, you will obtain a customized sensor.

#### 1. Dimensions in mm:



#### 2. Nominal resistance:

100 Ohm

500 Ohm

1000 Ohm

10000 Ohm

#### 3. Temperature range:

150°C

200°C

400°C

600°C

#### Wire material:

Enameled Copper Wire

Teflon insulated

Silver bare

Pt/Ni bare

#### Wire diameter:

0.2 mm

AWG 26/30/32  
Stranded Wire  
AWG 28/7

0.25 mm

0.2 mm

#### 4. Number of wires:

2-Wires

3-Wires

4-Wires

#### 5. Wire length:

5 mm

up to

1000 mm

#### 6. Tolerance:

DIN EN 60751  
Class B

DIN EN 60751  
Class A

#### 7. Metallised backside:

NiCr/Ni/Au  
-200°C + 400°C

Pt  
-200°C + 600°C

Your Sensor e.g.:



Special materials  
and sizes on request



TEMPERATURE



HUMIDITY



FLOW

# Platinum Temperature Sensors Order Information

**P 1 K 0. 5 2 0. 4 W. B. 0 1 0. M** | **Example**

### Specials

- T Substrate thickness 0.25 mm
- D Substrate thickness 0.38 mm
- R Round housing
- W Sintered powder
- M Metallised backside
- U Inverted welding
- S Special\*

### Connection length in mm

### Tolerance classes

- A Class DIN A
- B Class DIN B
- C 2 Class DIN B
- Y 1/3 Class DIN B
- P Pairs\*
- G Groups\*
- K Customer specific\*

### Extension type

- S SIL (single in line) tin solder
- P Overall (SMD)
- FC Tin-plated contacts
- W Wire
- SW Perpendicular leads
- FW Flat wire
- I Insulated contacts
- E Enameled wires
- L Insulated stranded wires
- K Customer specific\*

- 1P = Contacts tin coated, LMP lead contained
- 2P = Contacts tin coated, LMP lead free, RoHS conform
- 3P = Contacts tin coated, HMP, RoHS conform
- 4P = Contacts gold plated, solderable film

### Temperature range

- 1 -60°C to 150°C
- 2 -200°C to 200°C
- 3 -200°C to 300°C
- 4 -200°C to 400°C
- 6 -200°C to 600°C
- 7 -200°C to 750°C
- 8 -200°C to 850°C
- 10 -70°C to 1000°C

### Mechanical dimensions (see various dimensions) in mm

### Resistance value in ohm at 0°C

### Characteristic curve

- Pt 3850 ppm/K
- W Pt 3850 ppm/K (extended temperature range in class A)
- U Pt 3750 ppm/K
- G Pt 3911 ppm/K

### Material identification

- P | Platinum

\* Additional details, specifications required from the customer.

### Order example:

- P 1K0. 520. 4 W. B. 010. M**
- 1: Material identification = Platinum Temperature Sensor
  - 2: Resistance value in ohm = 1'000 Ω / 0°C
  - 3: Chip dimension = 5 mm x 2 mm
  - 4: Temperature range = + 400°C
  - 5: Extension = Wire connections (Ag, Ø 0.25 mm)
  - 6: Tolerance class = DIN EN 60751 class B
  - 7: Connection length = 10 mm
  - 8: Special = metallised backside

Specifications are subject to change without notice

